

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/012175 A1

(51) International Patent Classification⁷: **C01B 33/193,**
33/18

Kinugasa, Wako-cho, Wake-gun, Okayama 709-0441 (JP).
OYAMA, Hisayo [JP/JP]; 48-8, Yasuda, Himeji, Hyogo
670-0955 (JP).

(21) International Application Number:
PCT/TB2004/002431

(22) International Filing Date: 29 July 2004 (29.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-285163 1 August 2003 (01.08.2003) JP

(71) Applicant (for all designated States except US): **DSL**
JAPAN CO. LTD. [JP/JP]; 12F Shinjuku Monolith, 2-3-1
Nishi-Shinjuku, Shinjuku-ku, Tokyo 163-0938 (JP).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **NISHI, Shugo**
[JP/JP]; 1-3, Kuise Terajima 2-chome, Amagasaki, Hyogo
660-0813 (JP). **TOKUNAGA, Tatsuya** [JP/JP]; 592-1,

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: AMORPHOUS SILICA PARTICLES HAVING HIGH ABSORBING CAPABILITIES AND HIGH STRUCTURAL CHARACTERISTICS



(57) Abstract: The present invention provides amorphous silica particles having high oil absorbency and high structural characteristics, wherein the oil absorbency is hardly decreased even when a high load is applied to the amorphous silica particles. In particular, amorphous silica particles are provided, wherein the maximum value of $\Delta V_p / \Delta R_p$ (where V_p is the pore volume [mm^3/g] and R_p is the pore radius [nm]) is $20 \text{ mm}^3/\text{nm} \cdot \text{g}^{-1}$ or more in the pore distribution curve obtained by a benzene adsorption isotherm, and the pore peak radius when the $\Delta V_p / \Delta R_p$ value is maximum is from 20 nm or more to 100 nm or less.

WO 2005/012175 A1

WO 2005/012175 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.